

P.P.E. CAT.2: **EN ISO 20345:2022**

SIZE: 35/48 (2½/13)

MONDOPOINT: 11

MADE IN: CHINA

PICTURES

DESCRIPTION



TEXAS ESD S1PS SR FO LG
07538tgGSGF

Safety shoes compliant with the new EN ISO 20345:2022, made of fine perforated suede, microfibre reinforcements on the toe and heel, "FLEXGRIP+" bi-density PU sole with special heel compliant with the requirements for ladder grip (LG). Comfortable and breathable to always work easily.

FEATURES

UPPER:
fine perforated suede, microfibre reinforcement on the toe and heel.

LINING:
breathable micro-perforated 3D fabric.

REMOVABLE INSOLE:
antistatic in PU with ergonomic thermoforming.

ANTI-PERFORATION INSOLE:
made from zero-perforation ultralight textile fiber (PS - nail Ø 3.0 mm).

TOE CAP:
in non-magnetic fiberglass, insulating, resistant to 200J.

SOLE:
PU dual density with absorption of energy on the heel. **SR + FO + LG**

PLUS:
Second pair of colored laces included.



DETROIT ESD S1PS SR FO LG
07538tgNRGS

DETAILS

OUTSOLE

REMOVABLE INSOLE



LOGOS and DECORATIONS
made in microinjection.
UPPER made of fine perforated suede



REMOVABLE INSOLE
antistatic in PU with ergonomic thermoforming.



Microfibre **ANTI-ABRASION REINFORCEMENTS**
on toe and heel.

Dual density PU **OUTSOLE** with special design of the lugs which guarantee maximum grip in all flexion conditions. **SR + FO + LG**

P.P.E. CAT.2: **EN ISO 20345:2022**

SIZE: 35/48 (2½/13)

MONDOPOINT: 11

MADE IN: CHINA

PICTURES



FELIX ESD S1PS SR FO LG
07538tgGRVF



COLTON ESD S1PS SR FO LG
07538tgTAGI

DESCRIPTION

Safety shoes compliant with the new EN ISO 20345:2022, made of fine perforated suede, microfibre reinforcement on the heel and suede reinforcement on toe. "FLEXGRIP+" bi-density PU sole with special heel compliant with the requirements for ladder grip (LG). Comfortable and breathable to work always easily.

FEATURES

UPPER:

fine perforated suede, microfibre reinforcement on the heel and suede reinforcement on toe.

LINING:

breathable micro-perforated 3D fabric.

REMOVABLE INSOLE:

antistatic in PU with ergonomic thermoforming.

ANTI-PERFORATION INSOLE:

made from zero-perforation ultralight textile fiber (PS - nail Ø 3.0 mm).

TOE CAP:

in non-magnetic fiberglass, insulating, resistant to 200J.

SOLE:

PU dual density with absorption of energy on the hee. **SR + FO + LG**

PLUS:

Second pair of colored laces included.

DETAILS



LOGOS and DECORATIONS
made in microinjection.

UPPER made of fine perforated suede

OUTSOLE



Laminar profiles for greater slipping resistance.

Profiles engraved for a better grip on ladders (LG - heel height ≥ 10 mm).

Laminar profile to increase grip for SR test.

Dual density PU **OUTSOLE** with special design of the lugs which guarantee maximum grip in all flexion conditions. **SR + FO + LG**

REMOVABLE INSOLE





REMOVABLE INSOLE
antistatic in PU with ergonomic thermoforming.



Microfibre **ANTI-ABRASION REINFORCEMENT** on heel.

Suede **ANTI-ABRASION REINFORCEMENT** on toe.

USER MANUAL




MULTILINGUE USER MANUAL: (IT, EN, ES, DE, FR, BG, CS, ET, GR, HR, HU, LT, LV, NL, PL, PT, RO, SK, SL, SV)
Dimension: 120 x 165 mm

LABELLING



TEAMWORK TAPE
sewn on the tongue (15x60 mm)
and printed **ESD LABEL** on lace
hooks



COMPOSITION LABEL
applied to the right shoe
Size 28 x 28mm



"CE" LABEL
inside the tongue
Size 50 x 15mm



SIZE LABEL
sewn between upper and tongue
Size 17 x 14mm

PACKAGING



Cardboard **SPARCO TEAMWORK SHOE-BOX**.
Protective inner tissue paper.
Size: 343x188x123 mm
Recycling info at the bottom (PAP20 - valid for Italy only)



SHOE-BOX LABEL reporting product's features, certification,
batch number, code, QR-code and Barcode.
Size: 105x60 mm