<u>eparco</u>°

INDY-R 07539TgCol



MADE IN: CHINA

P.P.E. CAT.2: EN ISO 20345:2022

SIZE: 35/48 (2½/13)

SONOMA ESD S1PS SR FO LG

07539tgGSVF

PICTURES

DESCRIPTION

MONDOPOINT: 11

Safety shoes compliant with the new EN ISO 20345:2022, made of ultra-breathable perforated mesh, microfibre reinforcements on the toe and heel, "FLEXGRIP+" bi-density PU sole with special heel compliant with the requirements for ladder grip (LG).

Comfortable and ultra-breathable to always work easily.

FEATURES

UPPER:

ultra-breathable perforated mesh, microfibre reinforcement on the toe and heel.

LINING:

breathable micro-perforated 3D fabric.

REMOVABLE INSOLE:

antistatic in PU with ergonomic thermoforming.

ANTI-PERFORATION INSOLE:

made from zero-perforation ultralight textile fiber (PS - nail Ø 3.0 mm).

TOE CAP:

inon-magnetic fiberglass, insulating, resistant to 200J.

SOLE:

PU dual density with absorption of energy on the hee. **SR + F0 + LG**

PLUS:

Second pair of colored laces included.

EDMONTON ESD S1PS SR FO LG 07539tqTAGI

DETAILS

OUTSOLE

REMOVABLE INSOLE



LOGOS and DECORATIONS made in microinjection. UPPER made of ultra-breathable perforated mesh



Microfibre ANTI-ABRASION REINFORCEMENTS on toe and heel.



Dual density PU **OUTSOLE** with special design of the lugs which guarantee maximum grip in all flexion conditions. **SR + FO + LG**



REMOVABLE INSOLE antistatic in PU with ergonomic thermoforming.

<u>eparco</u>°

INDY-R 07539TgCol



P.P.E. CAT.2: EN ISO 20345:2022

SIZE: 35/48 (2½/13)

MONDOPOINT: 11

MADE IN: CHINA

PICTURES



DESCRIPTION

Safety shoes compliant with the new EN ISO 20345:2022, made of ultra-breathable perforated mesh, microfibre reinforcements on the toe and heel, "FLEXGRIP+" bi-density PU sole with special heel compliant with the requirements for ladder grip (LG).

Comfortable and ultra-breathable to always work easily.

FEATURES

UPPER:

ultra-breathable perforated mesh, microfibre reinforcement on the toe and heel.

LINING:

breathable micro-perforated 3D fabric.

REMOVABLE INSOLE:

antistatic in PU with ergonomic thermoforming.

ANTI-PERFORATION INSOLE:

made from zero-perforation ultralight textile fiber (PS - nail Ø 3.0 mm).

TOE CAP:

non-magnetic fiberglass, insulating, resistant to 200J.

SOLE:

PU dual density with absorption of energy on the hee. **SR+F0+LG**

PLUS:

Second pair of colored laces included.

DETAILS



LOGOS and DECORATIONS made in microinjection. UPPER made of ultra-breathable perforated mesh



Microfibre ANTI-ABRASION REINFORCEMENTS on toe and heel.

OUTSOLE



Dual density PU **OUTSOLE** with special design of the lugs which guarantee maximum grip in all flexion conditions. **SR + FO + LG**

REMOVABLE INSOLE



REMOVABLE INSOLE antistatic in PU with ergonomic thermoforming.



INDY-R 07539TgCol



P.P.E. CAT.2: EN ISO 20345:2022

SIZE: 35/48 (2½/13)

MONDOPOINT: 11

MADE IN: CHINA

USER MANUAL



he hodoser referred to in this information sheet our oths discussion. The manufactures declines are now	only provide the re	unuary level of protestion if used and maintained as descri-
e all'igges el'elemetan, se recomment contactio	the manufacture	at the following address:
Se other Column are	racioni (DE - 100 nel terminolije	BYHylana (10) - kely mail: mana-parastemanik.com
his safety biotomer complies with the Pensonal Proto also meets the requirements of the European stands	nive Equipment for and Electric States of	gulation (IU) 2014/ICUs innovaecement, combet, solidity ICO and it is certified by one of the following solidied books
Cities of his	alpha (00%) - 6 no	n (1887): Via Aquandismo Billo: 27029 Vigoruma (PV): Radj 21): Via Carlos Bilgini 216 - 20063 Comunes nel Naciglio «Nacumano Frankel: 48067 (per ambre 17 - France naturish nelsish am sundam his bar nitrami sentam, al 186
SSS SSS to performance and quality		
Category	Class	Additional requirements
u .	iel	Safety basis requirements
в	1	UE = Closed heef area = Architeks properly = Energy decorption of seatoregion
10	1	Un Upper soler peretration and absorption
EX (metal insert type P) or EXX (non-metal insert type PL) or EXX (non-metal insert type PQ)		\square - perhaption resistance according to the type closter solution
tu .		SE - Closed bool awa - Antically properly - Energy decorption of sastrongion
EE (metal insert type F) or EEE (more motal insert type FE) or EEE (more motal insert type FE)		Six perhapsion resistance according to the type cluster mobile
M .	-	El roderminieur al de whale batane
12' (metal insert type P) or 12's (men metal insert type PS) or 12's (non-metal insert type PS)	1	El custo resistence el decululo hadana
Clerc's Restorant made from leather and other materials, or	mindry all radios	er all polyments businesse
Clearly All polymeris (i.e. emisely resolded) including all n	dan (a minty	durine) feature
his safety between is designed to minimize the risk or compare form with a safe sending emissionment, and min of EN NO 20141-2012.	lajayahahasa allaa saapida	the inflationality the source starting use. It is designed to be present in pay ℓ as a soldered arrows which assumes the terms of the source of the sourc
	injug bandaling	alignois and snatking when wore in industrial and comme

INSTRUCTION	FOR USERS EN
idditional protection may be provided, and a identified on the product by it marking as led	
	Melinpade
serfacular emissioner (min. 1 180% metal insert i di 4.5 mm Canical Nati	
perforation resistance (min. 1100N) non-metal insert also filmen Control Nadi perforation resistance (min. 1100N & each single subset of NAN more metal insert :	
perforation resistance (min.) 100% & each single value of 600% mon motal insert : dr. E. Omer Cardinal Mail	
- Bestel	
Partially Conductive (maximum volutions (100 NO)	
Artistatis (recisions range of 100 kG to 1000 MC)	
- Indiana behinda	
Nationalational sile samples	14
Culti insulation of sole complex	
Energy absorption of seatington (38 insules)	
Note: residence	145
Metalanul protestian	-
Artile protection	89
Cutrovisiant	а
Snaff Cap almosium	16
Up revolution on commit the floor with physicism	
- iger	
Note persistive and saler description	MA.
- Cristi	
Residence to hot contact	HNO
Resistance to Earl of	PG PG
Lablergrip	16
As it is present to the the beatines where the reason has valided by the production for the production of the production	e seller and the purchaser to answer, where






MULTILANGUAGE USER MANUAL: (IT, EN, ES, DE, FR, BG, CS, ET, GR, HR, HU, LT, LV, NL, PL, PT, R0, SK, SL, SV)
Dimension: 120 x 165 mm

LABELLING



TEAMWORK TAPE sewn on the tongue (15x60 mm) and printed ESD LABEL on lace hook



COMPOSITION LABEL applied to the right shoe Size 28 x 28mm



"CE" LABEL inside the tongue Size 50 x 15mm



SIZE LABEL sewn between upper and tongue Size 17 x 14mm

PACKAGING





Cardboard **SPARCO TEAMWORK SHOE-BOX**.

Protective inner tissue paper.

Size: 343x188x123 mm

Recycling info at the bottom (PAP20 - valid for Italy only)



SHOE-BOX LABEL reporting product's features, certification, batch number, code, QR-code and Barcode.
Size. 105x60 mm