

LATEX EXAMINATION GLOVES, POWDERED, SENSITIVE



Reference

2514-XS	2514-M	2514-XL
2514-S	2514-L	

General Characteristics

Material: Natural Rubber	Sterility: Non sterile
Latex	High Comfort, dexterity and resistance
Color: Natural	Beaded cuff, thimbles ends
Available sizes:	micro-textured
XS, S, M, L, XL	Ambidextrous
	Single Use

Intended Purpose

Protection of the health professionals, patients and thirds against eventual contamination, for the prevention of disease ou damage, in hospital environment, clinics, laboratories, among others.

Classification

Medical Device of class I - non-sterile;
Personal Protective Equipment (PPE) of category I


Standards and Directives Applied

Medical Device of class I - non-sterile, in accordance with Regulation (EU) 2017/745 and Personal Protective Equipment of category I, in accordance with Regulation (EU) 2016/425.

Manufactured under the requirements of the Standards EN ISO 13485 and EN ISO 9001.

EN 455 1/2/3/4; EN 374-1/2/3*; ASTM F1671-07; EN 420:2003 + A1:2009; EN 980:2008; ISO 15223-1:2012; EN ISO 14971:2012; EN ISO 21171:2007; EN 1186, "Directive 2002/72/ CE".

Symbology Applied



Storage Precautions

Keep in a dry and powder-free local. Avoid humidity, sunlight and fluorescent light. Temperature not inferior to 10°C and not superior to 38°C.

Validity

5 Years, after manufactured's date

Logistic

Carton with 1000 units. Composed by 10 boxes with 100 units

Physical Characteristics

		Specifications	Inspection level AQL
Width (mm)	XS	70 - 75	S2 / AQL 4.0
	S	80 - 85	
	M	90 - 95	
	L	100 - 105	
	XL	110 - 115	
Length (mm)	All sizes	≥ 240	S2 / AQL 4.0
Thickness (mm)	Cuff	0,08 +/- 0,01	S2 / AQL 4.0
	Palm	0,08 +/- 0,01	
Weight (gr/glove)	XS	4,1 +/- 0,2	S2 / AQL 4.0
	S	4,5 +/- 0,2	
	M	5,0 +/- 0,2	
	L	5,4 +/- 0,2	
	XL	5,9 +/- 0,2	

Mechanical Characteristics

		Specifications	Inspection level AQL
Before aging	Tensile Strength	18 Mpa (min)	S2 / AQL 4.0
	Ultimate elongation	650% (min)	
After aging	Tensile Strength	14 Mpa (min)	
	Ultimate elongation	500% (min)	

Requirements AQL

Type	Non Conformities	Inspection level	AQL
Dimensions	Width, Length, Thickness	S2	4.0
Visual	Descoloration, dirtiness, spots	S4	4.0

Manufacturer

Raclac S. A.

*40% Sodium Hydroxide